




J.T.T.TECH CO.,LTD

www.jtt-tech.net

Industrial InkJet Coding Printers

Supports upto 2 printheads, 0.5 inch printhead

B62 Series



Sample Object for Print



Pharmaceutical



Electronics



Pipes



Wooden pallets



Foods



Case Coding



120m/min
high-speed printing



One customer one code,
exclusive ASIC encryption chip



One-click for the ink cost



Intelligent interface,
easy and fast



Access management,
privacy protection



Universal Master Control,
free combination

เครื่องพิมพ์วันที่ ผลิต วันหมดอายุ นัมเบอร์ริง
รหัสสินค้า ระบบ Thermal Ink Jet หน้าจอสัมผัส
ขนาด 7 นิ้ว มีให้เลือกตั้งแต่ 1,2,4 หัวพิมพ์ พิมพ์ได้
คมชัด ด้วยหมึกคุณภาพ (water base/solvent base)
เครื่องใช้งานง่าย เหมาะสำหรับติดตั้งบนสายพานการ
ผลิตสินค้า และระบบเครื่องทำงานอัตโนมัติ



J.T.T.TECH CO.,LTD

www.jtt-tech.net

Specifications:

| Project | Parameters |
|--------------------------------|--|
| Product Model | B62(1printhead,1*12.7mm) B62(2printheads, 2*12.7mm) B64(4printheads, 4*12.7mm) |
| Printing Technology | Thermal Ink Jet (TIJ) |
| Display | 7" Definition Touch Screen |
| Machine Interface | Support external network interface, USB, Serial port, USB flash drive, DB9, Bluetooth, WiFi |
| System language | Chinese, English, Thai, German, Arabic, Spanish, Russian, Japanese, Korean, etc. |
| Contact Method | Hall sensor trigger, photoelectric sensor trigger, continuous printing |
| External ports | Ethernet, USB, Photo cell, Encoder, Beacon, Power Adaptor |
| Status Alarm | Green=Read, Blue=Printing, Red = Alarm |
| Print Applications | Text, Number, Image, Logos, 2Dcode, Barcode, Date, Counter, Database, etc. |
| Barcode Type | Code128, Code128B, Code39, Ean8, Ean13, UPCA, UPCE, Ean128, INT2of5, ITF14, Code93, GS1RSS14 , GS1EAN128, GS-1 Truncated, GS1RSS14EX, GS1-StackedOmini, GS1StackedEx |
| 2 Code Type | Datamatrix, QR, GridMatrix, GS1DM, PDF417 |
| Input Method | Chinese intelligent Pinyin input, Chinese handwriting input Western input |
| Font Type | True type font, Dotmetrix font |
| Resolution | X direction DPI: 75/100/150/200/300/600/1200/2400 Y: direction DPI :300/600 |
| Number of printing line | 12.7mm maximum 5lines per printhead 25.4mm maximum 10lines per printhead |
| Printing heigh | 12.7mm, 25.4mm |
| Printing distance | 2-5mm (Distance between printhead and object) |
| Print Speed | Up to 120m/minute, speed adjustable based on the horizontal resolution |
| Optional Ink cartridge | Water base / Solvent base : 42ml. (Black, Blue, Red) |
| Grey level | 1-10 |
| Max Print size | 12.7mmprinthead:48mm*3200mm |
| Working Environment | Equipment Storage Temperature -20C°~55C°Working Temperature -5C°~35C° Humidity 10%~80% |
| Power Supply | Input: AC100~240V Output DC24V 4A |
| Max Pixel size | 566*12800px (Max 1000px x 12800px) |
| Memory size | 8 Gigabytes |
| Net Weight | Single head 4.60kg, Dual head 5.25kg Four-heads 6.730kg |

Contact: J.T.T. TECH CO.,LTD

1214-1216 M.6 Sukhumvit Rd, Samrongnua, Muang, Samutprakarn 10270

Tel: 02-7541860-1 Fax: 02-7541471

E-mail: jtt-tech@hotmail.com, jtt.sale@gmail.com